



Polymers


 Aromatic &
 Chemicals

**Fuel & Feeds
 Stock**

HEAVY END

| TYPICAL TEST | UNIT | SPEISIFICATION | TEST METHOD |
|--------------------|------------|----------------|-------------|
| Distillation Range | °C | | ASTM D-86 |
| IBP | °C | 160-180 | ASTM D-86 |
| 10% | °C | 175-193 | ASTM D-86 |
| 30% | °C | 187-209 | ASTM D-86 |
| 50% | °C | 206-230 | ASTM D-86 |
| 90% | °C | 286-330 | ASTM D-86 |
| FBP | °C | 333-370 | ASTM D-86 |
| Total Recovery | % | 96 | ASTM D-86 |
| Total Sulfur | ppm | 2000 Max. | ASTM D-5453 |
| color | - | 2 Max | ASTM D-1500 |
| Flash point | Centigrade | 59 Min. | ASTM D-93 |
| Specific Gravity | - | 0.77-0.83 | ASTM D-4052 |

HEAVYAROMATIC SPEISIFICATION

| TYPICAL TEST | UNIT | SPEISIFICATION | TEST METHOD |
|--------------------|---------|----------------|-------------|
| DENSITY @ 15.6 ° C | gr /cm3 | 0.8-0.95 | ASTM D-4052 |